
Prestige 100 Solo







- Easy to service and maintain with all components accessible from the front and flame inspection panel
- > Compact and lightweight
- Integrated non return flue valve saves space above the boiler installation
- Stainless steel heat exchanger for a long life, backed up by a 10-year heat exchanger warranty*
- Close load matching for more efficient use with a 6:1 turndown ratio

- Simple to operate with integrated ACVMax controls LCD that can operate two heating circuits or a four boiler cascade
- Optional pipework kits and low loss headers available
- Suitable for natural gas and LPG supplied with LPG kit for easy on site conversion

ACV UK Ltd

St. David's Drive, St. David's Business Park, Dalgety Bay, Fife, KY11 9PF uk.sales@acv.com | acv.com


Technical data and dimensions




ТҮРЕ	UNIT	Prestige 100 Solo
Part number		05648401
Fuel		Natural gas
Output power max (80/60°C)	kW	97.5
Output at 100% (50/30°C) G20	kW	104.5
Output power min (80/60°C) G20	kW	12.2
Voltage	V	230
Input max (heating) HCV	kW	109.89
Efficiency at 30% load (EN15502-1) – nett	%	108.1
Connection - heating	Ø"	1½ M
Flue connection	Ømm	100/150
Connection gas	Ø"	1 M
Water pressure drop boiler at Δt = 20°C	mbar	42
Gas flow rate (max output)	m³/h	10.5
Weight (empty)	kg	89
Max operating temperature	°C	87
Max service pressure heating (primary)	bar	4
Voltage	V	230
Standby loss ΔT 30K	W	139
Space heating energy efficiency class		А
Seasonal space heating efficiency	%	93
NOx class (EN15502)		6
NOx weighted (GCV) (EN15502)	mg/kWh	34.2
Sound power level indoors LWA	dB	62

Clearances	(minimum)	
Тор	300mm	
Left side	25mm	
Right side	25mm	
Below	220mm	







All dimensions in mm.